

CONNEX Cold Shrink Tube

For RF ½" & 7/8" connectors

RoHS compliant



Application

Manufactured from high-quality EPDM rubber, the CONNEX Cold Shrink Tube offers exceptional resistance to extreme temperatures, moisture, UV radiation (tested for more than 720 hours), and other environmental factors, ensuring long-lasting protection for your valuable connections. By achieving an IP67 rating, the CONNEX Cold Shrink Tube provides an impenetrable barrier against moisture, ensuring your connections remain dry and secure under the weather conditions of -40°C to +85°C.



General Specifications

Material	Silicone rubber
Cable type to	LLF Feeder LLX-CL Leaky LLF HiFlex
Cable size	½" & 7/8"
Color	Black
Mastic	Yes
Shrink ratio	4:1

Dimensions

Length before shrink	115mm 4.53 in
Length after shrink	130mm 5.12 in
Inner Diameter Before Shrink (ID)	40mm 1.57 in
Inner Diameter After Shrink (ID)	10mm 0.67 in
Thickness after shrink	3.1mm 0.12 in

Testing & Environmental

Operating temperature	-40°C to +85°C
Weatherproof resistance	IP67, based on ISO20653:2013
UV resistance	≥720Hours, based on ISO 4892-3

Packing Information

Bag width	260 mm 10.24 in
Bag length	320 mm 12.6 in
Packaging quantity and UOM	1 pcs
Weight gross	0.031 kg (0.068 lbs.)
Part number	CK-9734723



CONNEX Cold Shrink Tube are designed for optimal performance with NEK SEALINE RF Solutions