

**CONNEXK SECURECLAMP**  
**Radiating Clamp for LLX 1/2"**  
**Fire Retard Ring Polyamide**  
**RoHS**

**NEK SEALINE**  
Marine Industrial Cables of NEK Kabel AS

Suitable for NEK Sealine cables  
RF LLX-CL Leaky 1/2"



**Application**

CONNEXK SECURECLAMP Radiating Clamp is designed for exceptional reliability in extreme conditions, making it an ideal choice for harsh and outdoor applications. It operates across a wide temperature range, from -40°C to 85°C, ensuring consistent performance. With a simple installation process, the clamps can be quickly mounted using wall plugs and screws. The design allows for easy push-in mounting, where the clamp grips and locks securely with minimal pressure. Made with high-quality polyamide materials and compliant with UL94 V-0, these clamps maintain their fire-retardant properties under high temperatures or electrical loads.

**General Specifications**

Cable Type	LLX Leaky
Cable Size	1/2"
Clamp Material	Polyamide, Low Smoke Zero Halogen
Base Material	Polyamide, Low Smoke Zero Halogen
Clamp & Base Colour	Black
Accessories	Clamp with 80mm base, ST4.8125 screw, M630 wall plug, and fireproof ring.

**Dimensions**

Nominal Size	1/2 in
Base Height	80.0 mm (3.15 in)
Hanger Spacing (Max)	10.0 m (32.8 ft.)

**Testing & Environmental**

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Flammability	UL94 V-0

**Packing Information**

Height	180 mm (7.0 in)
Width	310 mm (12.2 in)
UOM	1 Pcs
Packaging	Bag
Gross Weight	0.04 kg (0.088 lbs.)
Part Number	CK- 9731944



CONNEX SECURECLAMP is designed for optimal performance with NEK SEALINE RF cables.

Explore the cables below for solutions for complete connectivity:

1/2" RF LLX Leaky cable SHF1 <https://www.nek-sealine.com/en/Product/Details/275257/>

1/2" RF LLX Leaky cable SHF2 <https://www.nek-sealine.com/en/Product/Details/287027/>

