



## ConMarin Plus 1/2" Feeder N-Male for RF LLF 1/2" High Quality - IP68 N-J1/2 - Feeder

### Application:

High quality connector for marine and offshore applications. Waterproof acc. to IP 68. Designed to connect our DNV-GL approved feeder cable RF LLF 1/2"

### Specifications:

Impedance:	50 [ $\Omega$ ]
Temperature range	- 40 til +125 [ $^{\circ}$ C]
Frequency range:	0 - 11 [GHz]
VSWR:	$\leq$ 1,20 [@ 2,5GHz]
Dielectric withstanding Voltage:	$\geq$ 2500 [V RMS, 50Hz] at Sea level
Dielectric resistant:	$\geq$ 5000 [M $\Omega$ ]
Resistant center contact:	$\leq$ 1,0 [m $\Omega$ ]
Resistant outer contact:	$\leq$ 1,0 [m $\Omega$ ]
Waterproof acc. to:	IP68
Durability:	mating cycles $\geq$ 500
Temperature range:	-40 - +85 [ $^{\circ}$ C]
Interface acc. to:	IEC 60169-16

### Construction:

Body:	Brass (Tri-Alloy)
Insulator:	PTFFE
Center conductor:	Phosphor Bronze (Ag)

Product no: 65402

