



ConMarin N-Male 7/8"

For: RF-LLF, RF-LLX & RF-LLF Hiflex

N-J7/8-1(WG)

50Ω

IP68

Application

Clamp Male-connector for outdoor use. Waterproof according to IP 68.
Fitting the RF-LLF 7/8", RF-LLX 7/8" & RF-LLF 7/8" Hiflex, 50Ω cable.



Temperature range	-40 – +85 [°C]
Interface	IEC 60169-16
Contact resistance	Outer contact: ≤ 0.25 [mΩ] Centre contact: ≤ 1.0 [mΩ]
Central pin	Brass/Phosphor bronze Ag ≥ 3 μm
Shell	Brass bar Tri-alloy ≥3μm
Insulator	PTFE
Rubber/waterproof ring	Silicone rubber
Other metal parts	Brass Ni ≥ 2.5 μm
Withstand Voltage	≥ 2000V, AC, 1Min
Impedance	50 [Ω]
Frequency range	DC-3 [GHz]
Dielectric resistant	≥ 5000 [MΩ]
VSWR	820 MHz – 2635 MHz: ≤ 1.12 2635 MHz – 3000 MHz: ≤ 1.15
Durability	≥ 500 [cycles]
Salt spray	Meet 48 Hours(5 % Salt Concentration)
Cables	7/8"
Product no.	65467

